

SPECIFICATIONS: PART No. 9935

Portable Diesel Indirect-Fired Heater



Includes:

- 25 ft. Flexible Heat Duct
- Remote Thermostat

Specifications:

Heat Input	110,000 BTU/Hr
Air flow	880 CFM
Fuel Type	Diesel / Kerosene / #1-2 Fuel Oil
Heat Output	91,900 BTU/Hr
Fuel Consumption	0.80 Gal/Hr (5.53 Lb/Hr)
Power supply	Phase: 1
	Voltage: 120 V
Electric consumption	Frequency: 60 Hz
	520 (W)
	5.76 (A)
Nozzle	0.60-80 deg S (US gal/h)
Max static pressure	0.5 WC
Recommended max. temp.	250
Pump pressure	167 psi
Adjustment of combustion air flap	a=0.32 inch
Tank capacity	10.8 Gal
Flue diameter	5.9 Inch
Compulsory flue draft	0.05 WC

FEATURES:

- Heat exchanger to keep exhaust gas and heated air separate
- 25 ft. length flexible heat duct
- Large capacity diesel fuel tanks provide hours of continuous operation
- Powerful fans ensure high static pressure allowing heater placement outdoors with clean heated air directed indoors
- Long life stainless steel combustion chamber
- Two stage pump for more reliable starts in sub-zero temperatures
- Electronic flame control
- Water resistant flame control box
- Automatic safety and control devices
- Durable powder coated finish
- Remote Thermostat included

For use with the following fuel types:

Kerosene
JP8 (JET A FUEL)
#1 AND #2 DIESEL
#1 AND #2 FUEL OIL

DO NOT USE BIO-DIESEL FUELS

Dimensions: 49.3"L x 20.0" W x 30.5" H
Net Weight: 94 lbs. Shipping weight: 200 lbs