



SPECIFICATIONS: PART No. 9976

200K BTU Portable Diesel Indirect-Fired Heater

Features + Benefits

- Burns diesel, kerosene and #1 and #2 fuel oil
- Large capacity fuel tank provides hours of uninterrupted operation
- Heat exchanger keeps exhaust gas and heated air separate
- Two-stage pump for more reliable starts in sub-zero temperatures
- Long-life stainless steel combustion chamber
- Electronic flame control
- Water-resistant flame control box
- Automatic safety and control devices
- Powerful fans pull massive amounts of cold air across a 4 loop heat exchanger, delivering clean and reliable indirect heat
- Durable powder-coated finish
- Heat capacity assumes temp rise of 20 to 60°F and 8ft. ceiling
- Equipped with heavy-duty 10in. pneumatic wheels



Includes:

- Duct Adaptor, 14" dia
- 25 ft. Flexible Heat Duct, 14" dia (qty1)
- Dual Duct Adaptor, 12" dia
- 25 ft. Flexible Heat Duct, 12" dia (qty 2)
- Remote Thermostat

Key Specs

Manufacturer's Warranty	1 year Limited
Ship Weight	176.0 lbs
BTU Output	200,000
Heating Capability (sq. ft.)	5,000
Volts	110
Amps	7.65
Blower (CFM)	1530
Heat Settings	One
Fuel Capacity (gal.)	Varies
Fuel Type	Diesel, kerosene, #1/#2 fuel oil
Fuel Consumption (gal./hr.)	1.48 Igniter Electronic

Dimensions L x W x H (in.) 51.6 x 20.1 x 38



Air Shelters USA, LLC

Phone: (800) 932-6003 Web: airsheltersusa.com Email: info@airsheltersusa.com